

Package: MajKMeans (via r-universe)

September 8, 2024

Type Package

Title k-Means Algorithm with a Majorization-Minimization Method

Version 0.1.0

Maintainer Sheikhi Ayyub <sheikhy.a@uk.ac.ir>

Description A hybrid of the K-means algorithm and a Majorization-Minimization method to introduce a robust clustering. The reference paper is: Julien Mairal, (2015) <doi:10.1137/140957639>. The two most important functions in package 'MajKMeans' are cluster_km() and cluster_MajKm(). cluster_km() clusters data without Majorization-Minimization and cluster_MajKm() clusters data with Majorization-Minimization method. Both of these functions calculate the sum of squares (SS) of clustering.

Imports MASS

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

NeedsCompilation no

Author Sheikhi Ayyub [aut, cre], Yaghoubi Mohammad Ali [aut]

Repository <https://sheikhi-a.r-universe.dev>

RemoteUrl <https://github.com/sheikhi-a/majkmeans>

RemoteRef HEAD

RemoteSha 2e2cb82dea9c6d60f3dd3aa5c5d7cdd18ef7a34b

Contents

clusters_km	2
clusters_MajKm	2
Euclid	3
kmeans	4

Index**5**

clusters_km	<i>clustering results of the k-mean algorithm</i>
-------------	---

Description

clusters data into two clusters. This function uses the kmeans function to cluster the data and exports the clustering results as well as the sum of square (SS) of clustering using the Euclidian distance.

Usage

```
clusters_km(x, k = 2)
```

Arguments

x	matrix of data (dim 1: samples (must be equal to dim 1 of X), dim 2: attributes (must be equal to dim 2 of X))
k	number of clusters (this version considers 2 clusters)

Value

sum of square (SS) of clustering

Examples

```
{
X=rbind(matrix(rnorm(1000*2 ,4,.1),1000,2),matrix(rnorm(1000*2, 3, 0.2),1000,2))
M <- X[sample(nrow(X), 2),]
clusters_km(X,2)
}
```

clusters_MajKm	<i>clustering results of the majorized k-mean algorithm</i>
----------------	---

Description

clusters data into two clusters with a majorization k-means This function uses a hybrid of the k-means and the majorization-minimization method to cluster the data and exports the clustering results as well as the sum of square (SS) of clustering

Arguments

x	matrix of data (dim 1: samples (must be equal to dim 1 of X), dim 2: attributes (must be equal to dim 2 of X))
k	number of clusters (this version considers 2 clusters)
La	the tunning parameter

Value

sum of square (SS) of clustering and the 'delta' (difference of two successive majorization function).

Examples

```
{
X=rbind(matrix(rnorm(1000*2),4,.1),1000,2),matrix(rnorm(1000*2),3,0.2),1000,2)
M <- X[sample(nrow(X), 2),]
clusters_MajK(X,2, 0.5)
}
```

Euclid

Euclidian distance

Description

Calculates the Euclidian distance between points. This function can use in kmeans function to do the clustering procedure using the Euclidian distance.

Usage

```
Euclid(x, mu)
```

Arguments

x matrix of data (dim 1: samples (must be equal to dim 1 of X), dim 2: attributes (must be equal to dim 2 of X))

mu initial selected centroids (randomly or another method).

Value

Euclidian distance between two points.

Examples

```
{
X=rbind(matrix(rnorm(1000*2),4,.1),1000,2),matrix(rnorm(1000*2),3,0.2),1000,2)
M <- X[sample(nrow(X), 2),]
Euclid(X,M)
}
```

kmeans	<i>k-means function</i>
--------	-------------------------

Description

k-means algorithm in clustering. This function export the clustered results based on one replication of the k-means method

Arguments

x	matrix of data (dim 1: samples (must be equal to dim 1 of X), dim 2: attributes (must be equal to dim 2 of X))
centers	initial seleted centroids (randomly or another method)
distFun	function (in this package the distance is Euclidian)
nItter	Number of itteration function

Value

clustered results based on k-means methods.

Examples

```
{
X=rbind(matrix(rnorm(1000*2 ,4,.1),1000,2),matrix(rnorm(1000*2, 3, 0.2),1000,2))
M <- X[sample(nrow(X), 2),]
kmeans(X,M, Euclid, 4)
}
```

Index

clusters_km, [2](#)
clusters_MajKm, [2](#)
Euclid, [3](#)
kmeans, [4](#)